

THRU-FLOW

PREMIUM DECKING SOLUTIONS

ThruFlow™ Legacy Specification Chart

Colours Available	Maple	Light Grey	Seafoam
-------------------	-------	------------	---------

Base Material	FRPP - Fibreglass Reinforced Polypropylene				
Sizes - (L x W x H)	inch	12 x 36 x 1.2	12 x 47.9 x 1.2	12 x 60 x 1.2	48 x 48.1 x 1.2
	mm	305 x 914 x 30	305 x 1219 x 30	305 x 1524 x 30	1219 x 1221 x 30
Support Span	inch	18	16	15	16
	mm	457	406	381	406
Weight	lbs	4.4	5.6	7.2	24.6
	Kg	2.0	2.5	3.3	11.2
Load Capacity at 0.125" Mid Span Deflection¹	lb _f	328	427	571	364
	N	1,459	1,899	2,540	1,619
Load Capacity - Peak Load¹	lb _f	1,387	1,594	1,974	1,452
	N	6,170	7,090	8,781	6,459
Concentrated Static Load - Peak Load⁴ <i>ASTM E661</i>	lb _f	715	683	964	881
	N	3,180	3,038	4,288	3,919
Coefficient of Friction² <i>ASTM D2394-83</i>	Static	0.78			
	Kinetic	0.76			
Thermal Expansion³ <i>ASTM D696-03</i>	1/°F	1.40 x 10 ⁻⁵			
	1/°C	2.52 x 10 ⁻⁵			
Light Availability⁴	Surface	%			
	18" Dock Height	%			
	60" Dock Height	%			
U/V Light Properties	U/V Stabilized by Additive				
Warranty	Lifetime Limited Warranty * See website for full warranty				

For full test reports please contact ThruFlow Inc.
700 Gillard St., Wallaceburg, ON, N8A 4L3
1-888-478-3569 / sales@thruflow.com

¹ UNB Wood Science and Technology Centre - Report# WSTC2014-044

² Cambridge Material Testing Limited - Report# 356155J-04

³ Cambridge Material Testing Limited - Report# 356155D-04

⁴ Cambridge Material Testing Limited - Report# 354661-04